

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

*Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)*

## SECTION 1: Identification of the substance/mixture and the company/undertaking

### 1.1 Product identifier

Lacquered, thin MDF/HDF (E1, E-LE, GPCO)

Fibreboard, LMDF/LHDF E-LE in the nominal thickness range of 1.8 mm - < 8.0 mm

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Packaging, FCPM, Door industry, Furniture industry: non-loaded furniture elements, for indoor use in dry conditions, interior fittings including furniture, back-panels etc.

### 1.3 Details of the supplier of the safety data sheet

Producing company: [KRONOSPAN-MOFA Hungary Ltd.](#)

Address: H-7700 Mohács, Budapesti országút 72.

Phone: +36-69-529-511

Fax: 36-69-529-539

Distributing company: [KRONOSPAN-MOFA Hungary Ltd.](#)

Address: H-7700 Mohács, Budapesti országút 72.

Phone: +36-69-529-511

Fax: +36-69-529-539

In case of emergency: Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ)

az Országos Kémiai Biztonsági Intézet (OKBI) osztálya

Address: H-1097 Budapest, Albert Flórián út 2-6.

Phone service on duty: +36-1-476-64-64;

E-mail: [ettsz@nnk.gov.hu](mailto:ettsz@nnk.gov.hu)

### 1.4 Emergency telephone number

+36-80-20-11-99

## SECTION 2: Hazardous identification

### 2.1 Classification of the substance or mixture

#### Appearance:

Different colours solid material.

This product is not hazardous in the form in which it is shipped by the manufacturer, but may become hazardous by dust generating downstream activities (e.g. grinding, sanding, cutting or pulverizing).

### 2.2 Label elements

Hazard pictograms and signal words

**Hazard statement:** Not Applicable

**Hazardous pictograms:** Not Applicable

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)

- Inhalation:** Abrasive action may cause wood dust to be generated that may be an irritant to the respiratory system.  
Lacquered fibreboard can emit minute amounts of gaseous formaldehyde and VOCs, whose intensity ventilation effect, and. decreases over time.
- Eye:** Abrasive action may cause wood dust to be generated that may be an irritant to the eyes.
- Skin:** Product may be an irritant and may cause contact dermatitis to wood sensitive individuals. Wash skin with soapy water. Seek medical advice for chronic symptoms of exposure.

**Signal word; H-sentences:** Not Applicable

Air saturated with dust released during its processing can form a combustible material.

- 315 Causes skin irritation
- 317 May cause an allergic skin reaction
- 319 Causes serious eye irritation
- 334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- 335 May cause respiratory irritation
- 350 May cause cancer
- 373 May cause damage to organs through prolonged or repeated exposure

**Precautionary statements, P-sentences:**

- 202 Do not handle until all safety precautions have been read and understood.
- 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- 220 Keep/Store away from clothing/.../combustible materials.
- 261 Avoid breathing dust/fume/gas/mist/vapours/ spray.
- 280 Wear protective gloves/protective clothing/eye protection/face protection.
- 302+352+305+351+338 IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- 308+337+314+340+264 IF exposed or concerned: If eye irritation persists: Get Medical advice/attention if you feel unwell. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash eye thoroughly after handling.
- 370+260 In case of fire do not breathe dust/fume/gas/mist/vapours/ spray.
- 402+232 Store in a dry place. Protect from moisture.

## 2.3 Other hazards

The components of this mixture do not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable.

### 3.2 Mixtures

Content: The product consists of (hard-, soft- and pine) wood fibre (>85%), hardened (effects of ammonium-nitrate and temperature) melamine-urea-formaldehyde artificial resin, and formaldehyde catching urea and hydrophobic effects (paraffin-emulsion) was added on the production. On the production the board top side got a (<20µm) thin film water based (VOC-poor: <0,3w/w%) lacquers and as finish coat acrylic UV-lacquer.

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)

## Composition / Hazardous material content:

	Name	CAS	EINECS	Concentration	Hazardous sign	H-phrases
1.	Formaldehyde	50-00-0	200-001-8	< 0.02 w/w%	-	332-302-312-314-315

H phrases mentioned in this part relate just to the hazardous component; not to the end-product. The H phrases of the end-product see at 2. and 16. parts.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information:** No special measures are required in relation to the finished product, but the following measures are required in relation to the dust generated during further processing of the product in order to avoid health risks:

**Inhalation:** Gaseous formaldehyde and wood dust may irritate respiratory system. Seek fresh air if necessary. Seek medical advice for chronic symptoms of exposure.

**Eye:** Gaseous formaldehyde and wood dust may irritate the eyes. Flush the eyes with water for 5 minutes if contact is made with wood fibre. After that go to eye-doctor if it is necessary.

**Skin:** Product may be an irritant and may cause contact dermatitis to wood sensitive individuals. Wash skin with soapy water.

**Ingestion:** The product at the current state of knowledge does not cause any damage, which would require first aid assistance.

### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 – Toxicological Information

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

The method of fire-fighting is determined by the fires of the environment.

Recommended materials for fighting the fire:

- Water,
- Fire-extinguishing powder
- Carbon dioxide,
- Foam.

### 5.2 Special hazards arising from the substance or mixture

In case of fire, dangerous products of disintegration can evolve (smoke, CO and CO<sub>2</sub>; NO<sub>x</sub>, NH<sub>3</sub>, aldehydes and VOCs). These products of disintegration should not be inhaled, they can be dangerous for human health.

During the processing of the product, wood dust is generated. Wood dust mixed in the air can form an explosive mixture above a certain concentration, avoid contact between the dust cloud and ignition source.

### 5.3 Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

*Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)*

protective clothing resistant to chemicals. In case of fighting the fire it is obligatory to use the following equipment: clothes from antistatic material covering the whole body, protective gloves and shoes, as well as an isolated breathing apparatus protecting the eyes and the face and also giving effective protection from dangerous products of disintegration.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal protection: Do not breathe dust. Only the people rescuing should be present at the working area. The usage of protective clothes, gloves, shoes and glasses is necessary, as well as that of breathing apparatus in case of the possible evolving of dangerous fumes and/or products of disintegration.

### 6.2 Environmental precautions

No special measures required.

### 6.3 Methods and material for containment and cleaning up

Not applicable for product in purchased form. Dust generated from sawing, sanding, drilling or routing this product may be vacuumed or shovelled for recovery or disposal. Dust clean-up and disposal activities should be accomplished in a manner to minimize of airborne dust. Dispose of the material collected according to regulations.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment

See Section 13 for disposal information

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

During some procedures of the product's manufacturing (grinding, dimensioning by sawing) dust can occur, which can form an explosive compound if mixed with air. During production processes, use suitable dust extraction equipment to minimize dust generation and accumulation. Clean the work area and equipment regularly.

### 7.2 Conditions for safe storage, including any incompatibilities

Storage should happen in a dry storing place with good airing, where the flat positioning of the plates can be secured. The product has to be protected from high temperatures, open fire and moisture. The product cannot be stored together with inflammable liquids. Suggested storage temperature: 15-30 °C and relative humidity 45-70%.

### 7.3 Specific end use(s)

During manufacturing – already at the place of origin – dust extraction and the replacement of the extracted air with fresh air has to be secured.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Dust needs to be controlled while cutting, sawing, drilling or other dust generating process are performed.

### 8.2. Exposure controls

During the manufacturing procedures with dust formation the usage of breathing apparatus of the class FFP1S is obligatory.

The determination of other special measures is not necessary. During handling of the product the related general rules of labour security and labour hygiene should be kept (e.g.: Safety glasses are recommended when cutting or sanding finished product.). With wood sensitive individuals, precautions should be taken to avoid skin contact.

For information, European limits:

Permissible Exposure Level wood dust: 1.0 mg/m<sup>3</sup>

Permissible Exposure Level formaldehyde: 0.6 mg/m<sup>3</sup> ppm

# MATERIAL SAFETY DATA SHEET

# kronospan

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)

Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Due to the explosive potential of dust when suspended in air, precautions should be taken during sanding, sawing or machining of products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.

Personal Protective Equipment Pictograms while downstream activities:



## SECTION 9: Physical and Chemical properties

### 9.1 Information on basic physical and chemical properties

physical state:	solid
colour:	different in specific product variations
odour:	mild characteristic
odour threshold:	not determined
pH:	no relevant
(4-5, 30 g sawdust of the substance in 500 ml boiling water 30 minutes after)	
melting point/freezing point:	not determined
initial boiling point and boiling range:	no relevant
flash point:	no relevant
evaporation rate:	no relevant
flammability (solid, gas):	no data available
upper/lower flammability or explosive limits:	not determined
vapour pressure:	no relevant
vapour density:	not relevant
density (20°C):	790 - 900 kg/m <sup>3</sup> , can differ in specific product variations
relative density:	no relevant
viscosity (20°C):	no relevant
solubility(ies):	not soluble in water
partition coefficient: n-octanol/water:	not determined
auto-ignition temperature:	341 °C (MSZ 14800-16:1992)
decomposition temperature:	no data available
burning time:	no data available
explosive properties:	not display
oxidising properties:	not display

### 9.2 Other information

No further information available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product is not reactive under normal conditions of use, storage and transport.

### 10.2 Chemical stability

The product is stable under normal recommended conditions of use and storage.

Conditions to be avoided: No decomposition if used according to specifications

### 10.3 Possibility of hazardous reactions

Hazardous material content: The product formaldehyde emission

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

*Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)*

at E1 class  $\leq 3.5 \text{ mg/m}^2\text{h}$  (measure in acc. with MSZ EN 12460-3:2016);  $\leq 0.124 \text{ }\mu\text{g/m}^3$  (measure in acc. with MSZ EN 717-2:2005)

The formaldehyde emission value of E-LE raw panels for CARB-EPA certified products is based on IKEA-IOS-MAT-0003 AA-10899-15 (2020-07-06), and CCR, title 17, 93120.2(a) Phase 2 and EPA TSCA Title VI. and Canada SOR/2021-148 actual (S)QCLs and below the limit value (ISO 12460-5:2016 Perforator value  $\leq 5.00 \text{ mg/100g}$  plate (@6.5% moisture) and ASTM D 6007-14 or ASTM E 1333-14 emission  $\leq 0.08 \text{ ppm}$ ),

If the products certified as GPCO, IKEA-IOS-MAT-0181 AA-218346-3 (2020-07-06) 1.4.2 Table 2. and below the actual (S)QCLs and limits according to the German Chemikalien-Verbotsverordnung Section 2.1 (emission  $\leq 0.1 \text{ ppm}$  according to ISO EN 16516:2018 and emission  $\leq 0.05 \text{ ppm}$  according to ISO EN 717-1:2005).

See also: our Technical (TDS) what is available on our website and our various manufacturer's declarations of conformity (GSoC)!

## 10.4 Conditions to avoid

Exposure to water, ignition source, high relative humidity and high temperature.

## 10.5 Incompatible materials

Acids, strong oxidizing agents.

## 10.6 Hazardous decomposition products

Hazardous decomposition may occur thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gases.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

No effects on toxicity known on the product.

Wood dust generated from handling, sanding or machining the product may cause nasal dryness, irritation, coughing and sinusitis. The International Agency for Research on Cancer (IARC) classifies wood dust as a human carcinogen (IARC Group 1).

**Acute effects:** No data.

The product itself may liberate formaldehyde if not stored properly and or wood dust if cut, sanded, or other abrasive action is applied.

**Chronic effects:** No data.

**Inhalation:** Studies suggest that cutting, sanding, or other abrasive action to this product may generate air born wood dust and or formaldehyde which may irritate the respiratory system or aggravate existing respiratory conditions. Users may become sensitized to wood dust or formaldehyde emissions over extended periods of time.

**Eye contact:** Wood fibre and or formaldehyde emissions from cutting, sanding, or other abrasive action may cause irritation of the eyes. Safety goggles are recommended.

**Dermal contact:** This product when cut, sanded, or abrasively altered may produce fibre that may be irritating to the skin for wood sensitized individuals. Gloves and or other dermal barriers are recommended if this occurs.

#### **Repeated dose toxicity**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

#### **Specific target organ toxicity - single exposure (STOT):**

Based on available data, the classification criteria are not met.

#### **Specific target organ toxicity - repeated exposure (STOT):**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard:**

Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

## SECTION 12: Ecological information

### 12.1 Toxicity

Not applicable for the product. Product is not classified as hazardous for the aquatic environment.

### 12.2 Persistence and degradability

No further relevant information available.

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

*Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)*

## 12.3 Bioaccumulative potential

Not applicable for the product.

## 12.4 Mobility in soil

No further relevant information available. General notes: generally not hazardous for water.

## 12.5 Results of PBT and vPvB assessment

Not applicable.

## 12.6 Endocrine disrupting properties

Not applicable.

## 12.7 Other adverse effects

No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of in an approved waste disposal facility and in accordance with local regulations.

Recommendation: EWC: 03 01 05

Dispose of packaging according to regulations on the disposal of packaging

## SECTION 14: Transport information

### 14.1 UN number

Not applicable. Product is not classified as dangerous during transport.

RID, ADR, ADN, IMDG, IATA void

### 14.2 UN proper shipping name

Not applicable.

RID, ADR, ADN, IMDG, IATA void

### 14.3 Transport hazard class(es)

Not applicable.

RID, ADR, ADN, IMDG, IATA void

### 14.4 Packing group

Not applicable.

RID, ADR, ADN, IMDG, IATA void

### 14.5 Environmental hazards

Not applicable.

RID, ADR, ADN, IMDG, IATA void

### 14.6 Special precautions for user

Not applicable.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency,

# MATERIAL SAFETY DATA SHEET

**kronospan**

KRONOSPAN-MOFA Hungary Ltd.

Origin: 10.07.2007

Date of update: 12.12.2022

Version: 4.0/EN

[In accordance with the criteria of Regulation No. 1907/2006 (REACH) and 878/2020 as amended]

*Lacquered, thin LMDF/LHDF (E1; E-LE, GPCO)*

amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 as amended.

Commission Regulation (EU) No 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC.

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives as amended.

European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste as amended.

## 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for product.

## SECTION 16: Other information

### Full text of H-Statements referred to under Section 3

Formaldehyde:

- 301 Toxic if swallowed
- 311 Toxic in contact with skin
- 314 Causes severe skin burns and eye damage.
- 317 May cause an allergic skin reaction
- 331 Toxic if inhaled
- 335 May cause respiratory irritation
- 341 Suspected of causing genetic defects
- 350 May cause cancer
- 370 Causes damage to organs

**SVHS:** No notification to European Chemical Agency (ECHA) as Thin LHDF has no SVHC on candidate list present in a concentration above 0.1% (w/w) and with a total amount of SVHC exceeding 1 ton per year

Small quantities of formaldehyde could be released, as traces of formaldehyde (<0.02% w/w) can be included in the Thin LHDF binders/additives.

**RoHS:** Compliancy with directive 2011/65/UE (Heavy metals).

### Education:

Before using the product, the user must be made aware of the occupational safety regulations for handling the product and must receive on-the-job training.

The information contained in the safety data sheet correspond to our present knowledge and the related Hungarian (EU conform) regulations.

However the safety-technical data sheet contains information about the safe usage of the product, which information does not represent a guarantee and a legally valid contractual relationship in terms of the technical information about applicability.